

JL500-ESFB7CP

Free Standing Bean to Cup Coffee Vending Machine

Features

- Reliable Performance
- User-friendly Interface
- High Security and Cost-Effective
- Easy for Cleaning
- 27" Touch Screen Display
- Dosage 0-14g is Acceptable for Brewing
- High Speed Mixer (Speed Adjustable)
- Fresh Tea Brewer

Beverage List

- Espresso
- Double Espresso
- Long Coffee
- Americano
- Cappuccino
- Latte
- Mocha
- Macciato
- Milk Cacao
- Cacao
- Hot Milk
- Red Tea
- Milk Tea
- Hot Water
- Instant Coffee
- Orange Juice
- Apple Juice
-



JL500-ESFB7CP coffee vending machine is specially designed for free standing vending market, mostly used in public areas like university, hospital, library, shopping mall, factory, railway station, airport etc.

JL500-ESFB7CP Free Standing Coffee Vending Machine

SPECIFICATIONS

User-Interface

27" Touch Screen LCD display
Dual Operating system: Linux / Android
Main VMC Application Framework Lib
Full MDB Protocol Support
QT GUI Framework
EVA/DTS Support for Vending Machine
Support 1080p Screen and 1080p Video Play
Support WIFI and 4G Dongle for Back Service Communication

Grinder

Made in Switzerland
EMH64 Professional Version
Flat Steel Disc (Diameter 64mm)
Life Span: 750,000 Portions
Bean Empty Detectable

Espresso Brewer

Jetinno International Patented
2PCs 24V DC Motors, Maximum Totally Current 5A
1PCs PTC Heater is Optional For Warming Up the Brewing Chamber
Dosage: 0~14 grams Ground Coffee
Zero Pollution, Don't Need to Take Out for Normal Cleaning
Brewer Removable for De-scale or Deep Cleaning
No Sensor and No Switch, absolutely No Malfunction
Main Structure is Made By 2mm Stainless Steel
Perfect Coffee Cake and Coffee Creamer

Hydraulic System

Jetinno Patented
700ml Stainless Steel Boiler
Pressure Sensor Design (Always Exact Brewing Pressure)
Gear Pump, Power Adjustable According to Pressure Sensor

Communication

MDB
EVA/DTS

Fresh Tea Brewer

Made in Switzerland
Suitable for Fresh Leaf Tea
Easy for Cleaning

Parameters

Maximum Power: 2700W
Fuse: 15A
Life Span: 125,000 Cycles
Mug Cup Table: 60-110mm
Cups: 500 cups
Instant Drinks Speed: 20s
Espresso Speed: 35s

Optional

Water Pump
Water Chiller
4G Module
Bill Validator
Coin Changer
Mobile Payment
Foot Wheels

Operating Environment

Voltage: 220V-240V AC, 50/60Hz
Temperature: 5° C to 50° C
Humidity: 10% to 95%

Dimensions and Weight

Dimension: 1830mm X 664mm X 700mm (H x W x D)
Weight: approx. 150kg